

- 1 Motherboards
- 2 Disk-Size SBCs
- 3 CPU Modules
- 4 PC/Io Pulse
- 5 CPU Card
- 6 Embedded Systems
- 7 Network Security Appliances

## CSB110-885D NEW



### Features

- Steel system supports IBASE IB885 3.5-inch Disk Size SBC
- Onboard AMD Athlon™ Neo X2 L325 dual-core processors
- Available in black color
- Rear panel I/O for USB, DVI, COM (optional VGA), KB/MS, LAN and DC-in jack

### Specifications

System Mainboard	IB885D
CPU Type	AMD Athlon™ Neo X2 L325 dual-core processors
CPU Package	ASB1
System Chipset	AMD M690E + SB600
Build-In Graphic Controller	ATI Radeon™ X1200 series
Memory	400/667MHz DDRII SDRAM up to 2GB
Chassis Color	Black
Construction	SECC
Front Panel External I/O	2x DB9 (Serial Ports) 1x DB15 (CRT) 2x USB 2.0 1x KB/MS connector 2x Audio Jack (Speaker & Microphone) Power LED HDD LED Reset Button On/Off Button
Rear Panel External I/O	1 x DVI 2x RJ45 (Gigabit LAN) 2x USB 2.0 2x PS2 (KB/MS) 1x DC-in Jack
Storage	1x 2.5" HDD drive bay 1 x CF Type II socket
Power Supply	60W AC-DC Power Adaptor Input Voltage : 90 ~ 264 Vac
Mounting	Optional wall mount kit
Dimensions	210mm(W) x 149mm(D) x 63mm(H)

### Environmental

Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20° ~ 80°C
Relative Humidity	5~90% @ 45°C, (non-condensing)
Vibration	CFD: 5 grms / 5~500Hz / random operation HDD: 0.25 grms / 5~500Hz / random operation

### Ordering Information

CSB110-885D	Signage System with IB885D 3.5" SBC, 2.5" HDD Bracket and 60W Power Adaptor
-------------	---

