

CMI110



Features

- Mini-ITX system supports IBASE DC-in motherboards (MI920, MB890 & MB500)
- Expandable for various applications
- Available in black color
- One 2.5" HDD drive bay
- Medium box design with 1x 5cm fan (optional)
- Wall mount kit included

Specifications

System Mainboard	MI920, MB890 & MB500
Construction	SECC
Chassis Color	Black
I/O Connectors	2x Front USB, 1x Front Power On/Off button, Rear side I/O Based on motherboard SPEC
Expansion Slots	1x PCI slot
Storage	1x 2.5" HDD drive bay
Power Supply	60W power adaptor
Mounting	Desktop or wall mount kit
Dimensions	202mm(W) x 200mm(D) x 111mm(H)

Environmental

Operating Temperature	0°C~45°C (32°F~140°F)
Relative Humidity	5 ~ 90% @ 40°C, (non-condensing)

Ordering Information

CMI110-500C	Chassis for MB500 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
CMI110-890C	Chassis for MB890 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
CMI110-920C	Chassis for MI920 Mini-ITX, w/ 60W power adaptor, 2.5" HDD holder
MI920EL-C6K	Intel® Celeron® M, 910GML Mini-ITX motherboard w/ VGA, DVI and 10/100
MI920EF	Socket 479 for Pentium® M/Celeron® M, 915GME Mini-ITX motherboard w/ VGA, DVI, Mini PCI-E, LVDS, 10/100 and PCI-E Gigabit LAN
MB890-R	Socket 479 for Pentium® M/Celeron® M, 852GM Mini-ITX motherboard w/ VGA and 10/100 LAN
MB890F-R	Socket 479 for Pentium® M/Celeron® M, 855GME Mini-ITX motherboard w/ VGA, 1394, TV-out and Gigabit LAN
MB500-R	AMD Geode LX700, 433MHz, CS5536 Mini-ITX motherboard w/ VGA and 10/100 LAN
MB500F-R	AMD Geode LX800, 500MHz, CS5536 Mini-ITX motherboard w/ VGA and dual 10/100 LAN,



Remarks: 1. ODM/OEM is available
2. Specifications are subject to change without prior notice.

- 1 Motherboards
- 2 Disk-Size SBCs
- 3 CPU Modules
- 4 PC/104 Puls
- 5 CPU Card
- 6 Embedded Systems
- 7 Network Security Appliance